



Radome Outside Diameters	Smooth Two-Piece Radome PVC	Smooth One-Piece Radome ABS	Smooth Multi-Part Radome	Multi-Part Multi-Sided Radome	Smooth Multi-Part Radome (Using ESSV panels)	RadomeFlex™
12"	X					
14"	X					
16"	X					
18"		X		X		
20"		X		X		
22"		X		X		
24"		X	X	X		X
26"		X	X	X		X
28"		X	X	X		X
30"		X	X	X		X
32"		X	X	X		X
34"		X	X	X		X
36"		X	X	X		X
38"		X	X	X		X
40"		X	X	X		X
42"		X	X	X		X
44"		X	X	X		X
46"		X	X	X		X
48"		X	X	X	X	X
50"		X	X	X	X	X
52"		X	X	X	X	X
54"			X	X	X	X
56"			X	X	X	X
58"			X	X	X	X
60"			X	X	X	X
Approximate Material Thickness	3/16" - 1/4"	1/8" - 3/16"	3/16"	3/16"	2-3/16"	3/16"
Maximum Height	12'	12'	12'	12'	12'	12'
Connection	Bolts	n/a	Bolts or Straps	Bolts or Straps	Bolts	Straps



SMOOTH TWO-PIECE




SMOOTH ONE-PIECE




SMOOTH MULTI-PART



MULTI-PART MULTI-SIDED



SMOOTH MULTI-PART (Using ESSV panels)



RADOMEFLEX™

*All radomes listed above (with the exception of RadomeFlex™) can be ventilated or perforated.

**Images are for illustration only. Contact Raycap | STEALTH® for exact details on your application and for diameters larger than listed for feasibility.